## 2024 **BRUTE FORCE® 300**







1.0.1.



. . . .

POWER		Fuel Capacity Electronic Power	3.2 gal
Engine	4-stroke, 1-cylinder, SOHC	Steering (EPS)	
Displacement	271cc	Turning Radius	9.2 ft
Bore x Stroke	72.7 x 65.2mm	Towing Capacity	500 lb
<b>Compression Ratio</b>	11.0:1	Total Rack Capacity	110 lb
Maximum Torque	15.9 lb-ft @ 6,500 rpm	Rack Capacity,	44/66 lb
Fuel System	Keihin CVK32 carburetor	Front/Rear	
Ignition	DC-CDI	Lighting	(2) 35W headlights, 5W taillight and 21W stoplight
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	DETAILS	
Final Drive	2WD, Shaft		

## **CAPABILITY**

Front Suspension / Wheel Travel	Independent double wishbone/5.2 in	Ov
Rear Suspension /	Swingarm/5.6 in	
Wheel Travel		
Front Tires	AT 22 x 7-10 Maxxis® tubeless	Sea
Rear Tires	AT 22 x 10-10 Maxxis® tubeless	Cu
Front Brakes	Dual 148mm discs	Wh
Rear Brakes	Single 148mm disc	Ins
Ground Clearance Starting System	6.1 in Electric	Со
Starting System		Wa

Frame Type	Double cradle, steel			
Track Front/Rear	33.5/32.7 in			
Overall Length	75.4 in			
Overall Width	42.5 in			
Overall Height	46.1 in			
Seat Height	33.3 in			
Curb Weight	535.8 lb*			
Wheelbase	45.9 in			
Instruments	Speedometer, odometer, clock, fuel gauge and coolant temp light			
Color Choices	Firecracker Red, Grayish Blue			
Warranty	12 Month Limited Warranty			



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit guatemala.kawasaki-la.com for full product details.