

2024 KLR® 650

Kawasaki
Let the Good Times Roll®



FIRECRACKER RED/METALLIC CARBON GRAY



PEARL CRYSTAL WHITE/METALLIC CARBON GRAY



POWER

Engine	4-Stroke, single cylinder, DOHC
Displacement	652cc
Bore x Stroke	100.0 x 83.0mm
Compression Ratio	9.8:1
Maximum Torque	39.1 lb-ft @ 4,500rpm
Fuel System	DFI® with 40mm throttle body
Ignition	CDI
Transmission	5-speed, return shift with wet multi-disc manual clutch
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System (ABS)

Front Tire	90/90-21
Rear Tire	130/80-17
Front Brakes	Single 300mm disc with 2-piston calipers (and ABS)
Rear Brakes	Single 240mm disc with single-piston caliper (and ABS)

PERFORMANCE

Front Suspension / Wheel Travel	41mm telescopic fork/ 7.9 in
Rear Suspension / Wheel Travel	Uni-Trak® single shock with adjustable rebound damping and adjustable spring preload/8.0 in

DETAILS

Frame Type	Tubular, semi-double cradle
Rake/Trail	30.0° /4.8 in
Overall Length	89.8 in
Overall Width	38.2 in
Overall Height	57.7/56.3 in (screen hi/lo)
Ground Clearance	8.3 in
Seat Height	34.3 in
Curb Weight	460.6 lb* (ABS), 456.2 lb* (non-ABS)
Fuel Capacity	6.1 gal
Wheelbase	60.6 in
Color Choices	Firecracker Red/Metallic Carbon Gray, Pearl Crystal White/Metallic Carbon Gray
Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit guatemala.kawasaki-la.com for full product details.