KLX®140R L









90/100-16

piston caliper

piston caliper

POWER

Engine 4-stroke single, SOHC, air-cooled

Displacement 144cc

Bore x Stroke 58.0 x 54.4mm

Compression

Ratio

9.5:1

Fuel System 20mm Keihin carburetor

Ignition Digital DC-CDI

Transmission 5-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

DETAILS

Rear Tire

Front Brakes

Rear Brakes

Frame Type High-tensile steel, box-section perimeter

Single 220mm petal disc with a dual-

Single 186mm petal disc with single-

Rake/Trail 27°/3.8 in

Overall Length 74.6 in

Overall Width 31.1 in

Overall Height 42.3 in

Ground

Clearance

Seat Height

Curb Weight

Fuel Capacity

Wheelbase 50.6 in

Color Choices Lime Green, Battle Gray

1.5 gal

10.0 in

31.5 in

209.4 lb*

Warranty 6 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel 33mm telescopic fork/7.1 in

Rear Suspension / Wheel Travel Uni-Trak® linkage system and single shock with piggyback reservoir, fully adjustable preload and 22-way rebound damping/7.1

ın

Front Tire 70/100-19

Scan with camera to view videos, key features and more.

