KLX®230R









POWER

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Fuel System DFI® with 32mm Keihin throttle body

Ignition TCBI Electronic Advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

Rear Tire 100/100-18

Front Brakes Single 240mm petal disc with a dual-

piston caliper

Rear Brakes Single 220mm petal disc with single-

piston caliper

PERFORMANCE

Front 37mm telescopic fork/9.8 in

Suspension /
Wheel Travel

Uni-Trak® linkage system and single s

Suspension / Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/9.9 in

Front Tire 80/100-21

DETAILS

Frame Type High-tensile steel, box-section perimeter

Rake/Trail 26.5°/4.4 in

Overall Length 80.5 in

Overall Width 33.1 in

Overall Height 47.2 in

Ground 11.8 in Clearance

Seat Height 36.4 in

Curb Weight 253.6 lb* / 262.3 lb* CA Model

Fuel Capacity 1.7 gal

Wheelbase 53.5 in

Color Choices Lime Green, Battle Gray

Warranty 6 Month Limited Warranty



