KLX®230 S









POWER

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

Maximum Torque 13.2 lb-ft @ 6,400 rpm

Fuel System

DFI® with 32mm throttle body

Ignition

TCBI with Electronic Advance

Transmission

6-speed

9.4:1

Final Drive

Sealed chain

Electronic Rider

Aids

Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel 37mm telescopic fork/7.8 in

Rear Suspension / Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.7 in

Front Tire

2.75 x 21

Rear Tire

4.10 x 18

Front Brakes

Single 240mm (265mm ABS Model) petal disc

with a dual-piston caliper (and ABS)

Rear Brakes

Single 220mm petal disc with single-piston

caliper (and ABS)

DETAILS

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.6°/3.7 in

Overall Length 81.8 in

Overall Width 33.2 in

Overall Height 44.8 in

Ground

Clearance

9.4 in

Seat Height 33.2 in

Curb Weight 291.0/293.2 lb* 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features ERGO-FIT®, LCD Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

Color Choices

Lime Green, Battle Gray

Warranty

12 Month Limited Warranty



