## KLX®230SM ABS







_	_			_
D	n	NA	/F	D
Г		W	Г	П

**Engine** 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

9.4:1

Compression

Ratio

Maximum Torque 13.2 lb-ft @ 6,400 rpm

DFI® with dual 32mm throttle bodies

Fuel System
Ignition

TCBI with Electronic Advance

**Transmission** 

6-speed

**Final Drive** 

Sealed chain

**Electronic Rider** 

Aids

Anti-lock Brake System (ABS)

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

Rear Suspension
/ Wheel Travel
wi

37mm inverted fork/7.4 in

Uni-Trak® linkage system and single shock with adjustable spring preload/8.7 in

Front Tire

**Rear Tire** 120/70-17

Front Brakes

Single 300mm petal disc with a dual-piston

caliper and ABS

**Rear Brakes** 

Single 220mm petal disc with single-piston

caliper and ABS

## **DETAILS**

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.9°/3.0 in

Overall Length 80.1 in

Overall Width 33.2 in

Overall Height 44.2 in

**Ground** 8.6 in

Clearance

Seat Height 33.0 in

Curb Weight 299.8/302.0 lb\* 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

**Special Features** | ERGO-FIT®, LCD Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

**Color Choices** Battle Gray

Warranty 12 Month Limited Warranty

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit guatemala.kawasaki-la.com for full product details.





110/70-17