## **KX**<sup>™</sup>250X







D	n	١	A		D
Г	u	N.	ľ	E	П

**Engine** 4-stroke single, DOHC, liquid-cooled

Displacement 249cc

**Bore x Stroke** 78.0 x 52.2mm

Compression

Ratio

14.1:1

DFI® with 44mm Keihin throttle body and **Fuel System** 

dual injectors

Ignition Digital CDI

**Transmission** 5-speed, return shift, with wet multi-disc

manual clutch

**Final Drive** 

**Electronic Rider** 

**Aids** 

Chain

Launch Control Mode

## **PERFORMANCE**

**Front** Suspension / **Wheel Travel**  48mm inverted telescopic coil-spring fork with 23-way compression damping and 20way rebound damping/12.4 in

Rear Suspension / **Wheel Travel** 

Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and

adjustable preload/12.4 in

**Front Tire** 80/100-21

**Rear Tire** 110/100-18

**Front Brakes** Single semi-floating 270mm Braking petal

disc with dual-piston caliper

**Rear Brakes** Single 240mm Braking petal disc with

single-piston caliper

## **DETAILS**

Aluminum perimeter **Frame Type** 

Rake/Trail 27.8° / 4.8 in

**Overall Length** 85.4 in

**Overall Width** 32.3 in

**Overall Height** 49.6 in

Ground 13.0 in Clearance

**Seat Height** 37.2 in

**Curb Weight** 230.1 lb\* without fuel / 240.2 lb\*

**Fuel Capacity** 1.64 gal

Wheelbase 58.3 in

**Color Choices** Lime Green

Not Available Warranty

Scan with camera to view videos. key features and more.

