





F)(1	W	F	R
ſ	ı	J١	ı	E	I۱

2-stroke single with exhaust power valve (KIPS), liquid-cooled

Displacement 84cc

Bore x Stroke 48.5 x 45.8mm

Compression

10.9:1 (low speed) / 9.0:1 (high speed)

Ratio

Fuel System 28mm Keihin carburetor

Ignition

CDI with Digital Advance

Transmission

6-speed, return shift, with wet multi-disc

manual clutch

Final Drive

Chain

PERFORMANCE

Front
Suspension /
Wheel Travel

36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / Wheel Travel Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in

Front Tire

70/100-17

Rear Tire 90/100-14

Front Brakes Single 220mm petal disc with dual-piston caliper

Rear Brakes Single 184mm petal disc with single-piston caliper

DETAILS

Frame Type	High-tensile steel perimeter design with subframe member			
Rake/Trail	29° /3.8 in			
Overall Length	72.0 in			
Overall Width	30.1 in			
Overall Height	43.3 in			
Ground Clearance	11.4 in			
Seat Height	32.7 in			
Curb Weight	164.4 lb*			
Fuel Capacity	1.32 gal			
Wheelbase	49.8 in			

Lime Green

Not Available





Color Choices

Warranty