

2024

MULE™ 4010 TRANS4x4® FE



POWER

|                         |   |
|-------------------------|---|
| Engine                  | 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled                          |
| Displacement            | 617cc   |
| Maximum Torque          | 34.7 lb-ft @ 2,500 rpm  |
| Bore x Stroke           | 2.99 x 2.68 in  |
| Compression Ratio       | 10:3:1  |
| Fuel System             | DFI® with 34mm Mikuni throttle body   |
| Transmission            | Continuously Variable Transmission (CVT) with (H,L,N,R)                       |
| Final Drive             | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| Engine Braking          | No  |
| Alternator Output (max) | 23 amp  |


CAPABILITY

|                                 |  |
|---------------------------------|--|
| Front Suspension / Wheel Travel | MacPherson Strut/3.9 in                          |
| Rear Suspension / Wheel Travel  | DeDion Axle/2.8 in                               |
| Front Tires                     | 23x11.00-10                                      |
| Rear Tires                      | 23x11.00-10                                      |
| Steering                        | Rack-and-pinion w/ Electric Power Steering (EPS) |
| Park Brake Type                 | Independent, Mechanical Drum                     |
| Front Brakes                    | Drum   |
| Rear Brakes                     | Drum   |

|                              |   |
|------------------------------|---|
| Ground Clearance             | 7.7 in  |
| Fuel Capacity                | 6.3 gal   |
| Turning Radius               | 12.8 ft   |
| Cargo Bed Dimensions (LxWxH) | 50.4 x 47.6 x 11.2 in (2-person) 30.3 x 47.6 x 11.2 in (4-person) |
| Cargo Bed Load Capacity      | 800 lb (2-person) 401 lb (4-person)                               |
| Payload Capacity             | 1,330 lb  |
| Seating Capacity             | 2-4   |
| Towing Capacity              | 1,200 lb  |
| Lighting                     | (2) Halogen headlights (2) tail/brake lights                      |

DETAILS

|                     |   |
|---------------------|---|
| Overall Length      | 128.5 in  |
| Overall Width       | 58.5 in   |
| Overall Height      | 78.1 in   |
| Curb Weight         | 1,614.1 lb*   |
| Wheelbase           | 85.2 in   |
| Instruments         | Parking brake warning light, coolant temperature warning light, horn, 12V DC outlet, fuel gauge, hour meter |
| Additional Features | Roof, Horn, Universal Key, High Visibility Orange Seatbelts   |
| Color Choices       | Bright White  |
| Warranty            | Kawasaki STRONG 3-Year Limited Warranty   |



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [guatemala.kawasaki-la.com](https://www.guatemala.kawasaki-la.com) for full product details.