MULE PRO-FXT™ 1000 LE CAMO







POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (L,H,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

90 amp

CAPABILITY

Front Suspension /

Wheel Travel

Double wishbone/11.0 in

Rear Suspension /

Wheel Travel

Double wishbone/10.1 in

Front Tires

26 x 9.00-12, radial

Rear Tires

26 x 11.00-12, radial

Steering

Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Ground Clearance

Fuel Capacity Turning Radius

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

12.6 in (max), 11.6 in (std)

7.9 gal

16.0 ft

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

person)

1,616.3 lb / 1,263.5 lb CA Model

3-person (1 row), 6 person (2 row)

2,000 lb

(2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 135.8 in

Overall Width 64.0 in

Overall Height 80.9 in

Curb Weight 1,922.8 lb* / 1,925 lb* CA Model

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip

meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Additional Features

Color Choices

Warranty

Roof, Additional Front Cup Holders

TRUETIMBER® STRATA

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

