
RIDGE® LIMITED HVAC







12.9 gal

15.0 ft

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,499/1,100 lb CA Model

3, bench seat

All-LED lighting

2.500 lb



POWER

4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled Engine

Displacement

Maximum Horsepower 92.0 hp1 @ 8,500 rpm **Maximum Torque** 65.8 lb-ft @ 5.500 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio 10.6:1

FFI **Fuel System**

Ignition TCBI with Digital Advance

Starting System Electric

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 4WD with locking rear differential, shaft

Engine Braking Yes

Alternator Output

(max)

85 amp

Electronic Rider Aids Power Modes, Economical Riding Indicator

DETAILS

Lighting

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Ladder type, tubular steel Frame

Overall Length 128.9 in **Overall Width** 64.0 in **Overall Height** 81.1 in

Dry Weight 2,022.0/2,024.2 lb** CA Model **Curb Weight** 2.127.8/2.130.0 lb* CA Model

Wheelbase 90.7 in

Instruments

Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil

pressure, water temperature)

Additional Features

Warranty

8" Garmin Tread®, WARN® VRX 45-S Powersport Winch, Full Cab with HVAC, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR^{TM} system compatible

Color Choices Metallic Shadow Gold

Kawasaki STRONG 3-Year Limited Warranty

CAPABILITY

Front Suspension / Wheel Travel

Long-Travel, Double Wishbone/12.7 in

Rear Suspension / Wheel Travel

Long-Travel, Double Wishbone/12.7 in

Front Tires Duro 27 x 9-14 **Rear Tires**

Duro 27 x 11-14

Wheel Type 14" Aluminum

Rack-and-pinion w/ Electric Power Steering (EPS)

Front Brakes

Steering

Dual hydraulic 249mm discs with two-piston calipers

Dual hydraulic 249mm discs with single-piston calipers

Rear Brakes

12.6/13.6 in (max preload); 12.6 in CA Model

Scan with camera to view videos, key features and more.

Ground Clearance



'Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit guatemala.kawasaki-la.com for full product details.