RIDGE® RANCH EDITION







12.9 gal

15.0 ft

34.6 x 49.0 x 12.8 in

1.000/600 lb CA Model

1,499/1,100 lb CA Model

3, bench seat

All-LED lighting

2.500 lb



POWER

4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled Engine

Displacement

Maximum Horsepower 92.0 hp1 @ 8,500 rpm **Maximum Torque** 65.8 lb-ft @ 5.500 rpm

Bore x Stroke 73.4 x 59.0mm

Compression Ratio 10.6:1

FFI **Fuel System**

TCBI with Digital Advance Ignition

Starting System Electric

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 4WD with locking rear differential, shaft

Engine Braking Yes

Alternator Output

(max)

85 amp

Electronic Rider Aids Power Modes, Economical Riding Indicator

DETAILS

Lighting

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Ladder type, tubular steel Frame

Overall Length 126.4 in **Overall Width** 64.0 in **Overall Height** 81.9 in

Dry Weight 1,808.1/1,810.3 lb** CA Model **Curb Weight** 1.909.5/1.911.7 lb* CA Model

Wheelbase 90.7 in

Instruments

Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding

Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil

pressure, water temperature)

Additional Features

Warranty

WARN® VRX 45 Powersport Winch, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system

compatible

Color Choices Metallic Stardust White

Kawasaki STRONG 3-Year Limited Warranty

CAPABILITY

Wheel Travel

Front Suspension / Long-Travel, Double Wishbone/12.7 in

Rear Suspension / Wheel Travel

Duro 27 x 9-14

Front Tires

Duro 27 x 11-14 14" Aluminum

Wheel Type

Rack-and-pinion w/ Electric Power Steering (EPS)

Long-Travel, Double Wishbone/12.7 in

Steering **Front Brakes**

Rear Tires

Dual hydraulic 249mm discs with two-piston calipers

Rear Brakes

Dual hydraulic 249mm discs with single-piston calipers

Ground Clearance

12.6/13.6 in (max preload); 12.6 in CA Model



