

2024

RIDGE® XR HVAC



- ICE GRAY
- METALLIC GRAYSTONE



POWER		Fuel Capacity	
Engine	4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled	Fuel Capacity	12.9 gal
Displacement	999cc	Turning Radius	15.0 ft
Maximum Horsepower	116.0 hp ¹ @ 8,500 rpm	Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in
Maximum Torque	73.8 lb-ft @ 8,000 rpm	Cargo Bed Load Capacity	1,000/600 lb CA Model
Bore x Stroke	73.4 x 59.0mm	Payload Capacity	1,499/1,100 lb CA Model
Compression Ratio	10.6:1	Seating Capacity	2, bucket seat
Fuel System	EFI	Towing Capacity	2,500 lb
Ignition	TCBI with Digital Advance	Lighting	All-LED lighting
Starting System	Electric	DETAILS	
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)		
Final Drive	Selectable 4WD with locking front/rear differential, shaft	Frame	Ladder type, tubular steel
Engine Braking	Yes	Overall Length	125.4 in
Alternator Output (max)	85 amp	Overall Width	64.0 in
Electronic Rider Aids	Power Modes, Economical Riding Indicator	Overall Height	82.3 in
CAPABILITY		Estimated Dry Weight	1,960.3/1,962.5 lb** CA Model
Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Curb Weight	2,066.1/2,068.3 lb* CA Model
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Wheelbase	90.7 in
Front Tires	Duro 30 x 10-14	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Rear Tires	Duro 30 x 10-14	Additional Features	Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLGY THE APP Powersports, USB ports, KQR™ system compatible
Wheel Type	14" Aluminum	Color Choices	Ice Gray, Metallic Graystone
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)	Warranty	Kawasaki STRONG 3-Year Limited Warranty
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers		
Ground Clearance	13.8/14.6 in (max preload); 13.8 in CA Model		

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

Specifications subject to change. Visit guatemala.kawasaki-la.com for full product details.