TERYX KRX® 1000 TRAIL EDITION







14.6 x 33.1 x 9.1 in

351 lb

781 lb

N/A

POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

Fuel System DFI® with two 50mm throttle bodies

TCBI with Flectronic Advance Ignition

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

DETAILS

Overall Height

Lighting

Cargo Bed

Capacity

Dimensions (LxWxH) Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

Frame Ladder type, tubular steel

Overall Length 133.3 in Overall Width 68.1 in

76.6 in **Curb Weight** 2,019.8 lb* / 2,022.0 lb* CA Model

Wheelbase 98.8 in

Instruments Multi-function digital meter with bar-style tachometer (2

(2) LED headlights, (2) LED taillights, LED stoplight

display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp.

Wheel Type Alloy with bead-lock wheels

Additional Features Roof, Front Bumper, Rear Bumper, Nerf Bars, WARN® VRX 45

Color Choices Cypher Camo Gray (Matte)/Super Black

6 Month Limited Warranty Warranty

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position

adjustable compression damping/18.6 in

Rear Suspension / **Wheel Travel**

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR **Rear Tires** Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Dual hydraulic discs with two-piston calipers **Front Brakes**

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.2 in (max), 13.6 in (std)

Fuel Capacity 10.6 gal **Turning Radius** 20.3 ft

Scan with camera to view videos. key features and more.

