

2024

# VULCAN® S CAFE ABS

**Kawasaki**  
Let the Good Times Roll®



METALLIC MATTE DARK GRAY/METALLIC FLAT SPARK BLACK



## POWER

<b>Engine</b>	4-stroke, 2-cylinder, DOHC, liquid-cooled
<b>Displacement</b>	649cc
<b>Bore x Stroke</b>	83.0 x 60.0mm
<b>Compression Ratio</b>	10.8:1
<b>Maximum Torque</b>	46.3 lb-ft @ 6,600 rpm
<b>Fuel System</b>	DFI® with 38mm throttle bodies (2), with sub-throttle valves
<b>Ignition</b>	TCBI with Electronic Advance
<b>Transmission</b>	6-speed with positive neutral finder
<b>Final Drive</b>	Sealed chain
<b>Electronic Rider Aids</b>	Economical Riding Indicator, Anti-lock Brake System (ABS)

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	41mm telescopic fork/5.1 in
<b>Rear Suspension / Wheel Travel</b>	Lay-down offset rear shock with linkage and adjustable preload/3.2 in

<b>Front Tire</b>	120/70x18
<b>Rear Tire</b>	160/60x17
<b>Front Brakes</b>	Single 300mm disc with twin-piston caliper, ABS
<b>Rear Brakes</b>	Single 250mm disc with single-piston caliper, ABS

## DETAILS

<b>Frame Type</b>	High-tensile steel diamond frame
<b>Rake/Trail</b>	31° / 4.7 in
<b>Overall Length</b>	90.9 in
<b>Overall Width</b>	34.6 in
<b>Overall Height</b>	44.5 in
<b>Ground Clearance</b>	5.1 in
<b>Seat Height</b>	27.8 in
<b>Curb Weight</b>	502.7 lb*
<b>Fuel Capacity</b>	3.7 gal
<b>Wheelbase</b>	62.0 in
<b>Color Choices</b>	Metallic Matte Dark Gray/Metallic Flat Spark Black
<b>Warranty</b>	12 Month Limited Warranty

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit guatemala.kawasaki-la.com for full product details.