Z500 ABS









POWER

Engine 4-stroke, Parallel Twin, DOHC, liquid-cooled

Displacement 451cc

Bore x Stroke 70.0 x 58.6mm

Compression

Maximum Horsepower

Ratio

Maximum 51.0 hp¹ @ 10,000 rpm

11 3.1

Maximum Torque

31.7 lb-ft @ 7,500 rpm

Fuel System

DFI® with dual 32mm throttle bodies

Ignition

TCBI with Electronic Advance

Transmission

6-speed

Final Drive

Sealed chain

Electronic Rider

Economical Riding Indicator, Anti-lock Brake System

(ABS)

PERFORMANCE

Front Suspension / Wheel Travel

41mm hydraulic telescopic fork/4.7 in

Rear Suspension / Wheel Travel Horizontal back-link with adjustable spring

preload/5.1 in

Front Tire

110/70-17

Rear Tire 150/60-17

Front Brakes

Single 310mm semi-floating disc with 2-piston

calipers and ABS

Rear Brakes

Single 220mm disc with single-piston caliper and

ABS

DETAILS

Frame Type Trellis, high-tensile steel

Rake/Trail 24.5°/3.6 in

Overall Length 78.5 in

Overall Width 31.5 in

Overall Height 41.5 in

Ground Clearance 5.7 in

Seat Height 30.9 in

Estimated Dry

Weight
Curb Weight

335.2 lb** / 337.4 lb** 50-State Model 366.0 lb* / 368.2 lb* 50-State Model

Fuel Capacity 3.7 gal

Wheelbase 54.1 in

Special Features ERGO-FIT®, LCD Instrumentation with Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Candy Lime Green/Metallic Flat Spark Black/

Metallic Graphite Gray

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.

