


2025

# KFX®90



| POWER             |  |
|-------------------|--|
| Engine            | 4-stroke, single-cylinder, air-cooled              |
| Displacement      | 89.9cc   |
| Bore x Stroke     | 47.0 x 51.8mm                                      |
| Compression Ratio | 10.0:1   |
| Maximum Torque    | N/A  |
| Fuel System       | Keihin PTE16 carburetor                            |
| Ignition          | Solid state CDI                                    |
| Transmission      | Automatic Continuously Variable Transmission (CVT) |
| Final Drive       | 2WD, chain   |

|                                 |                      |
|---------------------------------|----------------------|
| Steering                        | Conventional tie-rod |
| Electronic Power Steering (EPS) | No                   |
| Turning Radius                  | 8.9 ft               |
| Towing Capacity                 | N/A                  |
| Total Rack Capacity             | N/A                  |
| Rack Capacity, Front/Rear       | N/A                  |
| Lighting                        | N/A                  |

| CAPABILITY                      |                                      |
|---------------------------------|--------------------------------------|
| Front Suspension / Wheel Travel | Single A-arm with twin shocks/2.8 in |
| Rear Suspension / Wheel Travel  | Swingarm with single shock/2.9 in    |
| Front Tires                     | AT 18 x 7-8 tubeless                 |
| Rear Tires                      | AT 18 x 9-8 tubeless                 |
| Front Brakes                    | Dual mechanical drums                |
| Rear Brakes                     | Hydraulic disc                       |
| Ground Clearance                | 3.9 in                               |
| Starting System                 | Electric with back-up kick-starter   |
| Fuel Capacity                   | 1.4 gal                              |

| DETAILS          |                           |
|------------------|---------------------------|
| Frame Type       | Double-cradle, steel      |
| Tread Width      | 26.8/26.0 in              |
| Track Front/Rear | 26.8/26.0 in              |
| Overall Length   | 56.1 in                   |
| Overall Width    | 35.6 in                   |
| Overall Height   | 36.4 in                   |
| Seat Height      | 25.6 in                   |
| Curb Weight      | 269.0 lb*                 |
| Wheelbase        | 38.0 in                   |
| Instruments      | N/A                       |
| Color Choices    | Lime Green, Battle Gray   |
| Warranty         | 12 Month Limited Warranty |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki's KFX®50 is recommended for use only by persons 6 or older, and the KFX®90 is recommended for use only by persons 10 and older. All children under 16 riding ATVs should always have direct adult supervision. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to [www.atvsafety.org](http://www.atvsafety.org). ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [guatemala.kawasaki-la.com](http://guatemala.kawasaki-la.com) for full product details.