

2027

# KFX®90



- LIME GREEN
- BRIGHT WHITE



| POWER                           |                                                    | Ground Clearance                | 3.9 in                             |
|---------------------------------|----------------------------------------------------|---------------------------------|------------------------------------|
| Engine                          | 4-stroke, single-cylinder, air-cooled              | Starting System                 | Electric with back-up kick-starter |
| Displacement                    | 89.9cc                                             | Fuel Capacity                   | 1.4 gal                            |
| Bore x Stroke                   | 47.0 x 51.8mm                                      | Steering                        | Conventional tie-rod               |
| Compression Ratio               | 10.0:1                                             | Electronic Power Steering (EPS) | No                                 |
| Fuel System                     | Keihin PTE16 carburetor                            | Turning Radius                  | 8.9 ft                             |
| Ignition                        | Solid state CDI                                    | DETAILS                         |                                    |
| Transmission                    | Automatic Continuously Variable Transmission (CVT) | Frame Type                      | Double-cradle, steel               |
| Final Drive                     | 2WD, chain                                         | Tread Width                     | 26.8/26.0 in                       |
| CAPABILITY                      |                                                    | Track Front/Rear                | 26.8/26.0 in                       |
| Front Suspension / Wheel Travel | Single A-arm with twin shocks/2.8 in               | Overall Length                  | 56.1 in                            |
| Rear Suspension / Wheel Travel  | Swingarm with single shock/2.9 in                  | Overall Width                   | 35.6 in                            |
| Front Tires                     | AT 18 x 7-8 tubeless                               | Overall Height                  | 36.4 in                            |
| Rear Tires                      | AT 18 x 9-8 tubeless                               | Seat Height                     | 25.6 in                            |
| Front Brakes                    | Dual mechanical drums                              | Curb Weight                     | 269.0 lb*                          |
| Rear Brakes                     | Hydraulic disc                                     | Wheelbase                       | 38.0 in                            |
|                                 |                                                    | Color Choices                   | Lime Green, Bright White           |
|                                 |                                                    | Warranty                        | 12 Month Limited Warranty          |

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki's KFX®50 is intended for use only by persons 6 or older, and the KFX®90 is intended for use only by persons 10 and older. All children under 16 riding ATVs should always have direct adult supervision. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to [www.atvsafety.org](http://www.atvsafety.org). ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [guatemala.kawasaki-la.com](http://guatemala.kawasaki-la.com) for full product details.