UPDATED 2027

RIDGE® HVAC

Kawasaki
Let the Good Times Roll®

METALLIC MATTE WHITISH BEIGE/FLAT EBONY

METALLIC BLUISH GRAY/EBONY

POWER

Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled
Displacement	999cc
Maximum Horsepower	116.0 hp[1] @ 8,500 rpm
Maximum Torque	73.8 lb-ft @ 8,000 rpm
Bore x Stroke	73.4 x 59.0mm
Compression Ratio	10.6:1
Fuel System	EFI
Ignition	TCBI with Digital Advance
Starting System	Electric
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 4WD with locking front/rear differential, shaft
Engine Braking	Yes
Alternator Output (max)	85 amp
Electronic Rider Aids	Power Modes, Economical Riding Indicator

CAPABILITY

Front Suspension / Wheel Travel	Long-travel, Double wishbone/12.7 in
Rear Suspension / Wheel Travel	Long-travel, Double wishbone/12.7 in
Front Tires	SUNF 30 x 10-14
Rear Tires	SUNF 30 x 10-14
Wheel Type	14" Aluminum
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers
Ground Clearance	13.8/14.6 in (max preload); 13.8 in CA Model
Fuel Capacity	12.9 gal
Turning Radius	15.0 ft
Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in
Cargo Bed Load Capacity	1,000/600 lb CA Model
Payload Capacity	1,275/875 lb CA Model
Seating Capacity	3, bench seat
Towing Capacity	2,500 lb
Lighting	All-LED lighting

DETAILS

Frame	Ladder type, tubular steel
Overall Length	125.4 in
Overall Width	64.0 in
Overall Height	82.3 in
Estimated Dry Weight	2,033.0/2,035.2 lb** CA Model
Curb Weight	2,138.9/2,141.1 lb* CA Model
Wheelbase	90.7 in
Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Additional Features	4,500-lb winch with synthetic rope, Flip-up windshield, Full Cab with HVAC, Adjustable driver's seat, Front stabilizer bar, ERGO-FIT®, 8-in full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible
Color Choices	Metallic Matte Whitish Beige/Flat Ebony, Metallic Bluish Gray/ Ebony
Warranty	Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
[1]This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
Specifications subject to change. Visit guatemala.kawasaki-la.com for full product details.