

2024

RIDGE® XR HVAC



Kawasaki
Let the Good Times Roll®

- GRIS ICE
- METALLIC GRAYSTONE



POTENCIA

| | |
|-------------------------------------|--|
| Motor | 4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled |
| Cilindrada | 999cc |
| Potencia máxima | 116.0 hp ¹ @ 8,500 rpm |
| Par máximo | 73.8 lb·ft @ 8,000 rpm |
| Diámetro x Carrera | 73.4 x 59.0mm |
| Relación de compresión | 10.6:1 |
| Sistema de combustible | EFI |
| Ignition | TCBI with Digital Advance |
| Arranque | Electric |
| Transmisión | Continuously Variable Transmission (CVT) with (H,L,N,R) |
| Transmisión final | Selectable 4WD with locking front/rear differential, shaft |
| Freno motor | Yes |
| Salida del alternador (máx.) | 85 amp |
| Electronic Rider Aids | Power Modes, Economical Riding Indicator |

CAPACIDAD

| | |
|--|--|
| Suspensión delantera/ recorrido del neumático | Long-Travel, Double Wishbone/12.7 in |
| Suspensión trasera/ recorrido del neumático | Long-Travel, Double Wishbone/12.7 in |
| Neumáticos delanteros | Duro 30 x 10-14 |
| Neumáticos traseros | Duro 30 x 10-14 |
| Wheel Type | 14" Aluminum |
| Dirección | Rack-and-pinion w/ Electric Power Steering (EPS) |
| Freno delantero | Dual hydraulic 249mm discs with two-piston calipers |
| Freno trasero | Dual hydraulic 249mm discs with single-piston calipers |
| Altura libre al suelo | 13.8/14.6 in (max preload); 13.8 in CA Model |

| | |
|---|-------------------------|
| Capacidad de combustible | 12.9 gal |
| Radio de giro | 15.0 ft |
| Dimensiones del compartimento de carga (LxAxA) | 34.6 x 49.0 x 12.8 in |
| Capacidad de carga del compartimento de carga | 1,000/600 lb CA Model |
| Capacidad de carga útil | 1,499/1,100 lb CA Model |
| Capacidad de asientos | 2, bucket seat |
| Capacidad de remolque | 2,500 lb |
| Luces | All-LED lighting |

DETALLES

| | |
|------------------------------------|--|
| Cuadro | Ladder type, tubular steel |
| Longitud total | 125.4 in |
| Anchura total | 64.0 in |
| Altura total | 82.3 in |
| Peso seco estimado | 1,960.3/1,962.5 lb** CA Model |
| Peso en orden de marcha | 2,066.1/2,068.3 lb* CA Model |
| Distancia entre ejes | 90.7 in |
| Instrumentación | Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature) |
| Características adicionales | Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible |
| Opciones de color | Ice Gray, Metallic Graystone |
| Garantía | Kawasaki STRONG 3-Year Limited Warranty |

Escanear con
cámara para ver
vídeos, características
clave y más.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visite guatemala.kawasaki-la.com para obtener detalles completos del producto.